

# Accessories

## SUSPENSION



**80AA13**  
Single wire 1500mm long adjustable suspension kit.



**80AA1330**  
Single wire 3000mm long adjustable suspension kit.



**00AA16**  
3 poles-ceiling rose power cable. Cable length 2000mm.



**00AA165P**  
5 poles-ceiling rose power cable. Cable length 2000mm.



**80AA11**  
Electrified linear joint.



**80AA05**  
Electrified 2 ways joint 90°.



**80AA06**  
Electrified 3 ways joint.




**80AA07**  
Electrified 4 ways joint.



**80MC1000**: 1000mm  
**80MC2000**: 2000mm  
Blind connection module in aluminium with linear mechanical joints included. Enquire for other lengths.

## RECESSED



**80AAPIL**  
Header kit for recessed installation.



**80PL24**: for 24W (LP) / 48W (HP)  
**80PL30**: for 30W (LP) / 60W (HP)  
**80PL36**: for 36W (LP) / 72W (HP)  
**80PL42**: for 42W (LP)  
**80PL48**: for 48W (LP)  
**80PL54**: for 54W (LP)  
**80PL60**: for 60W (LP)  
**80PL66**: for 66W (LP)

Side aluminum profile recessing, also for continuous-row. Each item code is composed of 2 pieces of aluminum profile, joint plates and spacers for alignment. Stirrup brackets magnetically hold the Bright module into the profile for a trimless effect.

## WALL



**80AA15**  
Kit for wall installation.



**80AA151M**  
Kit for wall installation Bright 6W / 12W.