

DIMPLES

ID CODE: 48

DIMPLES is a recessed, suspended and ceiling mounted installations fixture. Characterized by its very shallow profile height of just 38mm, integrated drivers and unique aesthetics. The individual **microcells contain optics that can either be specified for offices applications** requiring low glare, or **general lighting applications** with broad lateral light distribution for core areas, including meeting rooms and break-out spaces.

DIMPLES is offered in a wide range of outputs and sizes, for direct only or bi-directional light distribution, making it an extremely versatile lighting collection and a huge step beyond the conventional edge lit lighting panels.





See also:

DIMPLES recessed p. 204









Design
Serge & Robert Cornelissen

FEATURES

-  Direct Emission
-  Direct/Indirect Emission
-  UGR <16; <22
-  IP 40




LED

-  3000K/4000K
-  >97 lm/W
-  CRI >90
-  Eye safety: RG0/RG1
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  CE
-  **A++ - A+**
-  5 years warranty

ON REQUEST

-  DALI - RDD code (verify the version)
-  BT Easy connect - BEM/BES code
-  Emergency kit 1/3 hour EM/EM 3h code

Specifications Built-in driver.

Optic

- Satin ABS reflectors with primary PC frosted diffuser, UGR<16
- PG version with additional frosted PC coplanar screen, UGR<22
- Double emission: direct / indirect

Body Frosted ABS body-diffuser with anodized aluminum base.

Colour ○ White RAL 9003 - Code: B



SUSPENDED - CEILING


DIMPLES

SUSPENDED
/CEILING


DIMPLES MINI

OPTIC

Satin ABS reflectors with primary PC frosted diffuser, UGR<16.




IP 40 A++




DIMPLES MINI PG

OPTIC

Satin ABS reflectors with primary PC frosted diffuser with additional frosted PC coplanar screen, UGR<22.



IP 40 A++



COLOUR TEMPERATURE

4000K

3000K

COD	💡	lm	mm
48DR10L490	10W	1040	152x152
48DR13L490	13W	1352	152x152

COD	💡	lm	mm
48DR10L390	10W	946	152x152
48DR13L390	13W	1230	152x152

COLOUR TEMPERATURE

4000K

3000K


COD	💡	lm	mm
48PG10L490	10W	988	152x152
48PG13L490	13W	1284	152x152

COD	💡	lm	mm
48PG10L390	10W	899	152x152
48PG13L390	13W	1168	152x152


DIMPLES

OPTIC

Satin ABS reflectors with primary PC frosted diffuser, UGR<16.



IP 40 A'



TEMPERATURE

4000K

3000K


COD	Im	mm
48DR44L490	44W	4665
		595x595

COD	Im	mm
48DR44L390	44W	4198
		595x595


DIMPLES DOUBLE EMISSION

OPTIC

Satin ABS reflectors with primary PC frosted diffuser, UGR<16, and upper diffuser for dual emission: direct / indirect.



IP 40 A'



DIRECT // INDIRECT EMISSION

mm	Power Direct Mod.	Power Indirect Mod.
595x595	44W	16W

TEMPERATURE

4000K

3000K


COD	Im	mm
48DI60L490	60W	6240
		595x595

COD	Im	mm
48DI60L390	60W	5678
		595x595


DIMPLES PG

OPTIC

Satin ABS reflectors with primary PC frosted diffuser with additional frosted PC coplanar screen, UGR<22.



IP 40 A'



COLOUR TEMPERATURE

4000K

3000K


COD	💡	lm	mm
48PG44L490	44W	4431	595x595

COD	💡	lm	mm
48PG44L390	44W	4032	595x595


DIMPLES PG DOUBLE EMISSION

OPTIC

Satin ABS reflectors with primary PC frosted diffuser with additional frosted PC coplanar screen, UGR<22 and upper diffuser for dual emission: direct / indirect.



IP 40 A'



DIRECT // INDIRECT EMISSION

mm	Power Direct Mod.	Power Indirect Mod.
595x595	44W	16W

COLOUR TEMPERATURE

4000K

3000K


COD	💡	lm	mm
48DI60PGL490	60W	5928	595x595

COD	💡	lm	mm
48DI60PGL390	60W	5394	595x595


DIMPLES LONG

OPTIC

Satin ABS reflectors with primary PC frosted diffuser, UGR<16.




IP 40 A'




DIMPLES LONG DOUBLE EMISSION

OPTIC

Satin ABS reflectors with primary PC frosted diffuser, UGR<16, and upper diffuser for dual emission: direct / indirect.



IP 40 A'



COLOUR TEMPERATURE

4000K

3000K

COD	💡	lm	mm
48DR35L490L	35W	3640	250x1195
48DR52L490L	52W	5408	250x1745

COD	💡	lm	mm
48DR35L390L	35W	3312	250x1195
48DR52L390L	52W	4921	250x1745

COLOUR TEMPERATURE

4000K

3000K

COD	💡	lm	mm
48DI52L490L	52W	5408	250x1195
48DI70L490L	70W	7280	250x1745

COD	💡	lm	mm
48DI52L390L	52W	4921	250x1195
48DI70L390L	70W	6625	250x1745


DIRECT // INDIRECT EMISSION

mm	Power Direct Mod.	Power Indirect Mod.
250x1195	35W	17W
250x1745	52W	18W


DIMPLES LONG PG

OPTIC

Satin ABS reflectors with primary PC frosted diffuser with additional frosted PC coplanar screen, UGR<22.



IP 40 A'



COLOUR TEMPERATURE

4000K

3000K


COD	💡	lm	mm
48PG35L490L	35W	3458	250x1195
48PG52L490L	52W	5138	250x1745

COD	💡	lm	mm
48PG35L390L	35W	3146	250x1195
48PG52L390L	52W	4675	250x1745


DIMPLES LONG PG DOUBLE EMISSION

OPTIC

Satin ABS reflectors with primary PC frosted diffuser with additional frosted PC coplanar screen, UGR<22 and upper diffuser for dual emission: direct / indirect.



IP 40 A'



DIRECT // INDIRECT EMISSION

mm	Power Direct Mod.	Power Indirect Mod.
250x1195	35W	17W
250x1745	52W	18W

COLOUR TEMPERATURE

4000K

3000K

COD	💡	lm	mm
48DI52PGL490L	52W	5138	250x1195
48DI70PGL490L	70W	6916	250x1745

COD	💡	lm	mm
48DI52PGL390L	52W	4675	250x1195
48DI70PGL390L	70W	6294	250x1745



48AA13
Single wire 1500mm long adjustable suspension kit.



48AA1330
Single wire 3000mm long adjustable suspension kit.




00AA16
3 poles-ceiling rose power. Cable length 2000mm.




00AA165P
5 poles-ceiling rose power. Cable length 2000mm.

OPTICS




PC version with body-diffuser in satin ABS and CUT-OFF effect diffuser for glare control.



PG version with additional frosted PC coplanar screen.

CONNECTION



The installation of devices is immediate thanks to the practical connector located in the back.

DIMPLES

ID CODE: 48

DIMPLES is a recessed, suspended and ceiling mounted installations fixture. Characterized by its very shallow profile height of just 38mm, integrated drivers and unique aesthetics. The individual **microcells contain optics that can either be specified for offices applications requiring low glare, or general lighting applications with broad lateral light distribution for core areas, including meeting rooms and break-out spaces.**

See also:




DIMPLES suspended/ceiling

p. 164









Design
Serge & Robert Cornelissen


FEATURES

-  Direct Emission
-  UGR <16; <22
-  IP 40




LED

-  3000K/4000K
-  >97 lm/W
-  CRI >90
-  Eye safety: RG0/RG1
-  Mac Adams 3
-  L80/B10 >50.000h

CERTIFICATIONS

-  CE
-  A++ - A+
-  5 years warranty

ON REQUEST

-  DALI - RDD code (verify the version)
-  BT Easy connect - BEM/BES code
-  Emergency kit 1/3 hour EM/EM 3h code

Specifications Built-in driver.

Optic

- Satin ABS reflectors with primary PC frosted diffuser, UGR<16
- PG version with additional frosted PC coplanar screen, UGR<22

Body Frosted ABS body-diffuser with anodized aluminum base.


Colour ○ White RAL 9003 - Code: B




DIMPLES

OPTIC

Satin ABS reflectors with primary PC frosted diffuser, UGR<16.



IP 40 A'



COLOUR TEMPERATURE

4000K

3000K


COD	W	lm	mm
48DR44L490	44W	4665	595x595

COD	W	lm	mm
48DR44L390	44W	4198	595x595


DIMPLES PG

OPTIC

Satin ABS reflectors with primary PC frosted diffuser with additional frosted PC coplanar screen, UGR<22.



IP 40 A'



COLOUR TEMPERATURE

4000K

3000K

COD	W	lm	mm
48PG44L490	44W	4431	595x595

COD	W	lm	mm
48PG44L390	44W	4032	595x595